

CABLE FAULT DETECTOR

- Reduces down time by quickly locating the problem
- Increases cable life by being non-intrusive and narrowly locating the problem area
- Eliminates the possibility of further damage to the cable by using a low level frequency signal for detection
- The transmitter output offers no risk to the user
- User friendly operation and indication
- Locate shorts in shielded or non-shielded cable
- Able to locate opens in non-shielded cable
- Finds shorts below 350 ohms
- Finds opens above 2,000 ohms



TRANSMITTER

ENCLOSURE DIMENSIONS	11-3/4" L x 6-1/4" W x 3-3/8" H (298.45 mm x 158.75 x 85.73)
ENCLOSURE TYPE	18 gauge Stainless Steel
UNIT WEIGHT	7 lbs (3.18 kg)
RECHARGING VOLTAGE	120VAC
BACKUP OPERATION	YES
MAX OUTPUT CURRENT	300 mA RMS
MAX OUTPUT VOLTAGE	8.5 VAC
OPERATING TEMPERATURE	-10 to 60 C
OUTPUTS	3 Conductor leads, 1 Ground lead, 1 Pilot wire lead
OUTPUT FREQUENCY	1.2 KHz (+/- 2%)
DISPLAY	LED Indicators
SELF TEST FEATURE	YES
WARRANTY	180 Days

DETECTOR

ENCLOSURE DIMENSIONS	4-3/4" L x 2-5/8" W x 2-1/4" D (120.65 mm x 66.68 mm x 57.15 mm)
ENCLOSURE TYPE	Molded ABS plastic with 18 gauge Stainless Steel
UNIT WEIGHT	16 oz. (453.59 g)
OPERATING VOLTAGE	9 VDC Battery
MAX OUTPUT CURRENT	50 mA
MAX OUTPUT VOLTAGE	2.5 VDC
OPERATING TEMPERATURE	-10 to 60 C
RECEIVER FREQUENCY	1.2 KHz (+/- 2%)
DISPLAY	LED Indicators